

Vinyl Tackboard Panels

Chatfield Clarke Vinyl Tackboard is made by machine laminating vinyl to a lightweight wood fiber panel, 1/2" thick, and wrapping the vinyl around the long edges. Panel edges are square cut, with beveled edges available on special order. Total weight of each panel is approximately 900 lbs. per 1000 sq. ft. The colors shown on our website and color cards are normally stocked, with other colors available on special order.

Chatfield Clarke Tackboard Panels install directly to drywall, providing a finished, usable wall surface ideal for education, business, hospitality, and healthcare settings.


To Request a Color Card call 909-823-4297 or email us at SUPPORT@CHATFIELDCLARKE.COM

Available as Perforated Tackboard Panels

Tackboard Panels that Breathe.

For those who like the benefits of perforated vinyls, Chatfield Clarke is able to perforate the tackboard after lamination, penetrating the vinyl adhesive right into the core.

Where mold and mildew is a concern, a breathable, permeable wall panel can help reduce the possibility for mold and mildew to thrive. Moisture is able to escape through a high quality permeable wall panel.



Chatfield Clarke's perforated wall panels are designed for greater breathability without compromising aesthetic or performance qualities. Additionally, perforated wall panels offer sound deadening properties, by breaking the surface of the vinyl.

Over 2,300 perforations are made in every square foot. Maximum perforation depth is 1/8".

RJF International

Corporation

www.chatfieldclarke.com

CHATFIELD CLARKE
Creative Wall Solutions

909-823-4297

Vinyl Tackboard Panels

Koroseal® Wallcoverings

54" Contract Vinyl Wallcoverings

3875 Embassy Parkway
Fairlawn, Ohio 44333

100% Water-Based Inks, Cadmium Free

	Group 1	Group 2
Physical Properties	U.S. Units	U.S. Units
Total Weight	15 oz. PLY 10 oz. PLY	15 or 18 oz. PLY 10 or 12 oz. PLY
Roll Width	53/54"	53/54"
Thickness	.007"	.0085"
Fabric	Sheeting	Sheeting
Federal Specification	CCC-W-408A, Type I	CCC-W-408A, Type I
CFFA Specification	CFFA-W-101-D	CFFA-W-101-D
NFPA 101 Life Safety Code	Type I, Class A Meets Class A when tested on GRC Board	Type I, Class A Meets Class A when tested on GRC Board



Larger Samples On Request

The Koroseal® brand wallcovering meets or exceeds all requirements of Federal Specifications CCC-W-408A and the CFFA Quality Standard For Vinyl Coated Fabric Wallcovering CFFA-W-101A, and the standard Classification of Wallcoverings by Durability Characteristics of ASTM F793-06 for the type and category classified including 24 hour cleanability tests based on ASTM method D1308.

Vinyl wall covering adhesive shall contain mildew inhibitors

Vinyl wallcovering shall be treated with antimicrobial to resist the growth of mildew and bacteria including staphylococcus aureus, streptovericallum reticulum (pink stain), and mixed fungal spore such as aspergillus niger, aspergillus flavus, penicillium funiculosum and Chaetomium globosum.

Colorations

The colors selected for this product result from research with the design community on color needs and trends for coordination with the latest in carpeting, laminates, furniture, and contract fabrics.

This product contains the Koroseal® Early Warning Effect® Formulation.
(Ask for the Early Warning Effect Information Bulletin for details.)

KOROKLEAR®

The flammability testing data, conclusions and recommendations in this report relate solely to measurements and descriptions of the properties of materials, products, or systems in response to heat and flame under controlled laboratory conditions and should not be considered or used for the description, appraisal, or regulations of the fire hazard of materials, products, or systems under actual fire condition.

Koroseal Wallcoverings, a division of RJF International Corporation
@RJF International Corporation © RJF International Corporation

Vinyl Tackboard Panels

Vinyl Tack Board Specification

Vinyl covered tackboard substrate shall be industrial insulation board 1/2" by full height and shall be manufactured specifically as a substrate for vinyl covered wall panels. The board shall be asphalt free, shall have an ironed-on coating, and have a density of 6 pounds per cubic foot. Edges are square without bevel (beveled available on request). The vinyl coatings shall be made of virgin vinyl calendared base color, weighing a minimum of 15 oz. per lineal yard. The coating shall be backed with sheeting or non-woven fabric. The vinyl wallcovering shall be mechanically laminated, with the long edges wrapped to the back of the tackboard. The panels will be applied over W' Gypsum board or 5/8" plywood sheeting. The vinyl covered tackboard shall be a class flame spread rating.

Reference brand: Chatfield Clarke (909) 823-4297

Care shall be taken in mounting the tackboard so that the texture of all panels will have the same orientation and color match.

Vinyl Tackboard Panels

Vinyl is machine laminated to a lightweight wood fiber panel 1/2" thick, and is wrapped around the long edges. Panel edges are normally square cut; beveled edges are available on special order. Total weight of panel is approximately 900 lbs. per 1000 sq. ft.

Colors shown are normally stocked. Other colors are available on special order.

Flame Resistant Industrial Insulation Board (FRIIB) - Available Upon Request

FR/1B(15-50-90) Class A fire rating on the coated side and tested in accordance with ASTM E84 under File R-4019.

Standard Sizes

48" x	84"	96"	102"	108"	120"	144"
	7'	8'	8.5'	9'	10'	12'

Test Result On Completed Panels

When tested in conformance with specifications set forth in ASTM Designation E-84, vinyl covered tackboards yielded the following results:

Flame Spread 65
Smoke Density..... 175-350*

*The numerical results shown relate solely to measurement in response to heat and flame under controlled laboratory conditions and should not be considered or used to reflex hazards presented by this or any other material under actual conditions.