

Fire Resistant Industrial Insulation Board





SAFFTY DATA SHEET INDUSTRIAL BOARDS

Section V - Fire Fighting measures

Flash Point:

200°C (wood dust)

Auto-Inflammation Temperature:

>400°C

Flammable Limits in air:

Upper Flammable Limit (UFL): No object

Lower Flammable Limit (LFL):

No object

Flammability Classification:

B2 (DIN 4102) Not Applicable

Rate of Burning

Specific Dangers

When in contact with an ignition source, wood dust can be an explosion hazard.

Combustion products:

Fire gives off normal combustion products.

Fire Fighting Agents:

Use dry powder, foam and water spray or appropriate extinguishing media for surrounding materials on

Fire Fighting Procedures:

Wear self-contained breathing apparatus and full protective clothing (see section 8).

Section VI - Accidental release measures

Containment:

No special measure.

Clean-up:

No special measure.

Disposal:

The finished product is a wood-based solid. Follow all local, municipal, provincial, state and federal regulations. To remove, use standard means approved for disposal. Dispose in a landfill or use any

other method prescribed by regulation.

Section VII - Handling and storage

Handling:

Dust can form an explosive mixture in air. Provide appropriate exhaust ventilation at machinery and at places where dust can be generated. Use personal protective equipment as required (see section 8). Avoid frequent or prolonged inhalation of wood dust. Wear the appropriate respiratory protection against dust in poorly ventilated areas and if TLV is exceeded (see Sections 2 and 8). Use good safety and industrial hygiene practices. Avoid contact with humidity and water. Presence of water may lead

to mold growth.

Storage:

Store flat, in a dry, well ventilated place and away from sources of excessive heat. Product should be

protected from the weather and direct sunlight.

Section VIII - Exposure controls/personal protection

Component	Weight %	TLV (m/m ³)	PEL (m/m ³)
Wood Fiber	>92	Not established	Not established
Coating	<1	Not established	Not established
Starch	<5	10	Total: 15 Respirable: 5
Wax fumes	<2	Fumes: 2	Fumes: 2
Wood Dust from sawing		0.5	Total: 5 Respirable: 5

ENGINEERING CONTROLS: Provide sufficient ventilation, i.e., enough to control airborne dust levels. Use ventilation to keep dust concentrations below permissible exposure limits. If cutting or trimming with power tools, dust collectors and local ventilation should be used. Avoid unnecessary exposure to dust and handle with care. Keep work area clean of dust by using an industrial vacuum cleaner with high efficiency filter or wetting down area with water. Never use compressed air and avoid dry sweeping.

If engineering controls are not possible, use safety glasses, gloves and dust respirator mask. Wear a NIOSH/MSHA approved respirator with cartridges in poorly ventilated areas or if TLV is exceeded.



SAFETY DATA SHEET INDUSTRIAL BOARDS

Section IX - Physical and chemical properties

Appearance at 25°C:

Odor:

Solid Neutral

pH:

No object

Density:

0.20 to 0.28 g/cm³

Melting Point:

No object

Freezing Point: Boiling Point: No object No object

Boiling Point: Evaporation Rate:

No object

Vapor Tension: Vapor Density:

No object No object

Relative Density (water = 1):

< 1

Solubility:

Insoluble in water Not measured

Decomposition Temperature: VOC

Maya

None

Section X – Stability and reactivity

Stability:

Stable.

Condition to avoid:

Contact with moisture and humidity may alter the product and even cause some mold development.

Incompatibility:

None known Will not occur

Hazardous Polymerization Hazardous Decomposition

The decomposition products are those expected from wood. These decomposition products may

include carbon oxides ad carbon particles. Thermal-oxidative degradation of wood produces irritating

fumes and gases.

Section XI - Toxicological information

Acute Effects:

None are known for the product. However, direct contact with any dust, including wood dust, can

Chronic Effects/Carcinogenicity

mildly irritate mucous membranes of your nose and eyes. None are known for the product. None are known for the product. However, repeated contact with wood dust can cause skin irritation, dermatitis or respiratory sensitization or irritation, because of the quinolic content of some wood

essence.

Section XII - Ecological Information

Environmental Toxicity: Ecotoxicity Value:

This product has no known adverse effect on ecology

ity Value: Not determined

Section XIII - Disposal considerations

Disposal:

The finished product is a wood-based solid. It may be recycled in local facilities. If unable to recycle dispose of the material in accordance with all local, municipal, provincial, state and federal regulations. Use standard means approved for disposal. Dispose in a landfill or use any other method prescribed by regulation.



SAFETY DATA SHEET INDUSTRIAL BOARDS

Section XIV – Transport information

U.S. DOT INFORMATION:

Not a hazardous material per DOT shipping requirements. Not classified or regulated.

Shipping Name:

Same as product name.

Hazard Class:

Not classified.

UN/NA #:

None / Not classified.

Packing Group

None.

Label (s) Required GGVSeb/MDG-Code

Not applicable.

Not classified.

ICAO/IATA-DGR

Not classified.

RID/ADR

None.

ADNR None.

Canadian Transportation of Dangerous Goods (TDG): Not a dangerous good.

Section XV - Regulatory information

Canada:

WHMIS Classification: Not a controlled product

All the ingredients are part f the Domestic Substance List (DSL)

United State:

All the ingredients contained in the product are included in U.S. Environmental Protection Agency's

Toxic Substances Control Act Chemical Substance Inventory

This product does not contain hazardous component as per WHMIS and OSHA, 29 CFR 1910.1200, SARA 302, 304 and 313, CERCLA CAA section 112 or RCRA hazardous legislations.

As per OSHA and WHMIS the above product is considered a consumable item and do not require MSDS. However we want to disclose as much as possible information relating to health and safety, to ensure that the product is handled and used properly. This MSDS contains valuable information for safe handling and proper use of the product. This MSDS should be retained and available for employees and other users.

European Union

Dangerous Substances Directive 67/548/EEC

R- Phrase(s): R36/37/38

(2001/59/EC)

s-Phrase(s): None Known

(2006/102/EC)

Section XVI - Other information

Caution!

Dust can cause eyes, skin and respiratory tract irritations. Cut and trim with a razor knife or hand saw to minimize dust levels. Avoid cutting with Power tools, because they generate high dust levels. Power tools must be equipped with a dust collection system. Wear eye, skin and respiratory protection as necessary per working conditions (see section 8). If eye contact occurs flush with water for 15 to 20 minutes. Do not ingest. If ingested, call a physician. KEEP OUT OF REACH OF CHILDREN.

NFPA Ratings: Health 1; Fire 0; Reactivity 0; Personal protection E (Safety glasses, gloves and dust respirator mask).

HMIS Ratings: Health 1; Fire 0; Reactivity 0; Personal protection E (Safety glasses, gloves and dust respirator mask)

NFPA and HMIS hazard category: 0= minimal, 1= Slight, 2 = Moderate, 3 = Serious, 4= Severe

Prepared by:

F. Bossé

Phone number:

514-364-8768

Revision date:

05 June 2015

Since this product is a "Manufactured Article". Building Products of Canada Corp. is not required by law to produce a Material Safety Data Sheet. This Material Safety Data Sheet is provided as customer service information. The recommendations and data presented are believed to be reliable. However, no warranty is expressed or implied regarding the accuracy of the data or the results obtained from the use of this information.

Safety Data Sheet (SDS) - Flame Retardant Coating

Flame retardant coating

Identification

Product Identifier

WT-102 flame retardant coating with adhesion abilities

Other means of Identification

Recommended use

Refer to manufacturer sell sheet

Recommended restrictions

Refer to manufacturer sell sheet

Manufacturer name

Firetect, Inc.

Address

28298 Constellation Road

Valencia, CA 91355

Country Phone

USA 661-295-3473

Fax E-mail Website

661-295-3880 info@firetect.com

www.firetect.com

Hazard(s) Identification

Emergency overview

Irritant.

Classification

Hazard symbol

Category 5. No symbol.

Signal word

Warning.

Potential health effects

Inhalation

Over-exposure may cause irritation. If not breathing, give artificial respiration.

Seek medical attention.

Eyes/Skin

Cleanse affected areas with mild soap and water. If irritation develops, seek

medical attention.

Ingestion

If drowsy or unconscious, place victim on left side with head down. Do not give

anything by mouth; seek medical attention.

Environmental hazards

Health:

No known significant environmental effects.

NFPA/HMIS classification

Flammability:

0 0

Reactivity:

0

0-Least, 1-Slight, 2-Moderate, 4-Extreme

Composition/Information on ingredients

Chemical name	CAS number	Percent
Water	7732-18-5	37-46%
Ammonium Polyphosphate	68333-79-9	18-25%
Pentaerythritol	155-77-5	3-12%
Melamine	108-78-1	7-13%
Other ingredients (Trade secret per 29 CFR 1910.1200) NO REPORTABLE HAZARDOUS INGREDIENTS	-	4-35%

4. First-aid measures

Inhalation

Remove person to fresh air. If necessary, seek advice of a

physician.

Skin contact

Wash skin with soap and water. Launder clothing before

Eye contact

In case of eye contact, flush with running water for at least 15 minutes. If irritation persists, seek advice of a physician.

Ingestion

If swallowed, induce vomiting and seek medical attention.

Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing media For dry solids use water foam, CO2, or dry chemical fire-fighting apparatus.

Specific hazards arising from

None. None.

the substance or mixture

WT-102 Flame Retardant Coating

Special protective equipment and precautions for fire-fighters Closed container exposed to heat may cause rupture due to pressure build-up.

6. Accidental release measures

Personnel precautions **Environmental precautions** Cleanup measures

None.

Avoid runoff into storm sewers, ditches, and waterways.

Flush spilled material into suitable retaining areas or containers with large quantities of water. Small amounts may be absorbed into appropriate absorbent. Dispose of product in accordance with applicable local, county,

state and federal regulation.

7. Handling and storage

Precautions for safe handling **Engineering controls**

Avoid breathing mist. Avoid prolonged skin contact. Use local exhaust ventilation if sprayed inside. Otherwise,

general ventilation is adequate.

Conditions for safe storage

Store upright in original sealed containers and in a cool, dry

location away from light and strong frost.

Storage temperature

Shelf life

Storage should not exceed 80°F or fall below 40°F. Do not allow to freeze.

Shelf life is one year, if containers are unopened.

Exposure controls/Personal protection

VOC

47 Grams/Liter

Exposure controls

Use appropriate engineering controls such as proper ventilation. Where such systems are not effective, wear suitable personal protective equipment, which performs satisfactorily and meets OSHA or other recognized standards.

Personal protective equipment

Eye/Face protection

Wear goggles to avoid overspray and splashing. Eye and face protection should be in accordance with OSHA 29 CFR 1910.133.

Hand/Arm protection Respiratory protection Rubber or plastic gloves are recommended.

Use an N-95 or P-95 mask. If sprayed, wear an air-purifying respirator approved by NIOSH in accordance with OSHA 29 CFR 1910.134(d)(1)(ii). If used in a confined area, a full-face, powered air-purifying respirator (PAPR) or suppliedair respirator (SAR) is recommended. Use respirators in accordance with 29 CFR

1910.134(d)(3)(i)(A) Table 1, 29 CFR 1910.134(d)(3)(iii)(B) and 29 CFR

1910.134(d)(3)(iv)(B).

Physical and chemical properties

Appearance

Physical state

Liquid.

Color

Color base and tinted black or white.

Odor

Very faint odor.

Odor threshold

Not applicable.

% volatile by vol

Freezing point **Boiling point** Specific gravity 32°F

212°F 1.08

Evaporation rate

Less than water.

Vapor pressure

None.

Vapor density Flashpoint

Equal to water. Not Applicable

10. Stability and reactivity

Reactivity

None.

Chemical stability

Stable.

Incompatible materials

Strong oxidizers.

	Decomposition materials	Carbon dioxide, carbon monoxide.
11. Toxico	exicological information	
	Acute toxicity	
	Potential health effects	
	Inhalation	May be harmful if inhaled. Short-term exposure may cause
	,	irritation of nose, throat and lungs.
	Eyes/Skin	May be harmful in contact with eyes/skin. Short-term
		exposure may cause irritation.
	Ingestion	May be harmful if swallowed. Possible stomach irritation and
		nausea.
12. Ec	ological information	
	Ecotoxicity	No data available.
	Persistence and degradability	No data available.
	Bioaccumulative potential	No data available.
	Mobility in soil	No data available.
	Other adverse effects	No data available.
13. Di	sposal considerations	
	Waste disposal of product	Do not discharge product into storm or waste water sewer systems. Dispose of product in accordance with applicable local, county, state and federal regs.
	Contaminated packaging	Dispose of in accordance with federal, state, and local regulations.
	Container disposal	Plastic pails are recyclable. Rinse well before recycling or disposal. Dispose of i
		accordance with federal, state, and local regulations. Contact local authorities
		for further information.
14. Tr	ansport information	
	Land transport	
	USDOT	Non-hazardous product. Not regulated.
	Marine transport	
	IMDG	Non-hazardous product. Not regulated.
	Air transport	
	IATA	Non-hazardous product. Not regulated.
15. Re	egulatory information	
	Additional safety, health	Not applicable.
	and environmental regulations	
16. Ot	ther information	
	•	nmunication Standard 29 CFR 1910.1200 and prepared to GHS.
	Preparation information	

Prepared by

Disclaimer

Firetect ®, Inc.

It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information given is presented in good faith and believed to be correct as of the date hereof, based on available data, material components, and similar materials. Firetect®, Inc. cannot anticipate conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used.